



महाराष्ट्र शासन
SIR J. J. GROUP OF HOSPITALS, BYCULLA,
MUMBAI - 400 008
Medical Store
सर ज.जी. समुह रुग्णालये, भायखला, मुंबई-४००००८
Tel.No.०२२२३७३९१०३, ०२२२३२२२४५३, ०२२२३७३५५५५
Email id-jjhmedicalstore@gmail.com



No. JJH/SS/QTN/१७ /2026

Date :- 16 / 07 / 2026

Sub : Quotation for the supply of Surgical items (Open Quotation)

Sir,

You are requested to submit your lowest bid for Surgical items. The quotation should reach this office in a sealed envelope on or before 24 / 07 / 2026 till 5.00 pm. Quotation is also published on www.ggmccjjh.com

The Dean, Sir J. J. Group of Hospitals, Mumbai reserves the right to Accept, Recall or Reject any or all quotations without assigning any reason. Other instructions and terms & conditions regarding quotation are mentioned below the Surgical items list.

Sr No	Name of Item	Specification	Packaging	Rate per pc. (including GST)	MRP
1	Disposable Syringe 50ml	Single Use. Sterile. No leakage. Non traumatic plunger. Latex free. Non toxic. Non pyrogenic. BP/ISO/ISI /CE STANDARDS 50 ml			
2	T-Piece	For use in recovery for the delivery of oxygen - Connects to 15 mm ET tube connector/ laryngeal mask - Fitted with 22 mm male / 15 mm female patient port - 6" flexible corrugated tube oxygen reservoir with oxygen supply port along with cap - Sterile and individually packed			
3	Epidural Set No.18	1. Epidural Catheter should be made up of polyurethane with radiopaque line, open distal tip or closed distal tip with 3 laterals eyes. Markings every centimetre from 5 to 20cm from the distal tip. 2. 1 catheter connector Easy-lock type 3. 1 Tuohy needle - 90mm long, with plastic hub 4.1 Catheter guide which connects into the needle hub and facilitates the insertion of the catheter into the epidural space 1. Epidural Catheter should be made up of polyurethane with radiopaque line, open distal tip or closed distal tip with 3 laterals eyes. Markings every centimetre from 5.5 , smudged marked at 11cm from the distal tip. 2. 1 catheter connector Easy-lock type 3. 1 Tuohy needle - 90mm long, with plastic hub 4.1 Catheter guide which connects into the needle hub and facilitates the insertion of the catheter into the epidural space 5. 0.2 Åµm flat filter 6. 10ml syringe for loss of resistance(LOR) technique 7. 1 label for catheter identification Size:18G			
4	Laryngoscope Adult	Should be LED laryngoscope set, adult, macintosh type, Stainless steel blades with removable led lamp. Handle and blades are made of 304 grade stainless steel.Dull/matt finish. Supplied with 4 blades size 1, 2, 3 and 4 and two batteries for handle. Should provide with 1 spare led lamp and batteries			
5	Laryngoscope Paediatric	Should be LED laryngoscope set, adult, Miller Type, Stainless steel blades with removable led lamp. Handle and blades are made of 304 grade stainless steel.Dull/matt finish. Supplied with 4 blades size 0,00,1 and 2, two batteries for handle. Should provide with 1 spare led lamp and batteries.			

6	Intercostal Draining System (All size)	Catheter should be provided with trocar for easy penetration and flat handle of a trocar catheter for easy maneuverability and controlled insertion. Catheter should be kink-resistant smooth finish PVC with streamline, radio-opaque line, flat handle to facilitate easy maneuverability, markings provided at 5, 10, 15 and 20 cm from the distal tip to help ascertain the depth of penetration. Thermosensitive material used in these equipments softens with body temperature. Safety stop in cannula with tip-toe radiopaque strip. Proximal end should be fitted with an universal tapered connector for easy connection to the drainage bag. Water sealed drainage system for intercostal drainage, sterile pyrogen free disposable (ICD Bags) bag. Should be available sterile, individually double packed in a peelable pouch. (Intercostal draining system with trocar and bag size-All size)			
7	Swivel Mount Catheter	Flexible, light weight, corrugated or smooth bore, PVC tube (often 15 cm length) used to connect endotracheal / tracheostomy tubes to breathing circuit. 22mm standard female/15mm male patient-end swivel connector, 15mm/22mm circuit end connector, low dead space and optically lock ports for gas sampling.			
8	Biopsy Gun (All Size)	Automated spring Loaded core Biopsy instrument disposable Constructed from medical-grade stainless steel with plastic or lightweight metal housings. needle gauges 16G-20G, Needle Lengths 10cm-25cm, penetration depths 10mm-22mm, Sample Notch- Often 1.8 cm to 2.0 cm.			
9	Scalp Vein Set (All Size)	Sterile, siliconised, thin walled, short bevel needle with colour coded butterfly 20g			
10	Endotracheal Tube No. 5,5.5,6	Should be available as a transparent tube with radiopaque line in extra-soft PVC. The distal end of the tube should be bevelled at 37° - 10°. The tube should have clear distance markings A standard male ISO adaptor 15 mm to connect the endotracheal tube to the ventilator The distal end of the tube should be bevelled at 37°-10 5mm, 5.5mm, 6mm ID			
11	Sterile Disposable Needle (All Size)	Single use Sterile, surface should be extremely smooth, the needle point is extremely sharp. Color coded, individually blister packed, hypodermic needle 1 Inch			
12	PICC Catheter 4Fr	Intracavitary ECG derivation device CT easy with pressure injection up to 5cc/s and 325 PSI with radiopaque biostable PUR 4FR-600mm with NDD technique & Metallic stylet with repair kit. Safety Echogenic introducer needle 21G x 7cm • 1 straight Nitinol guidewire 0.46*50cm • Should be European CE Certified.			
13	Anatomical Face Mask 0,1,2,3,4	an inflatable cuff for comfort, a standard 22mm connector, and a disposable or autoclavable (up to 137°C) design, typically made from non-toxic silicone or PVC. 0,1,2,3,4			
14	Surgical Blade (All Size)	Surgical Blade / B.P. Blade Pre sterile wrapped with antirust paper in aluminium foil ISI mark No. (All Size) Surgical Blades Pre-Sterile With Gamma Radiation For Handle No. 4 Size CE certified			
15	Irrigation Balloon	Irrigation Balloon			
16	Colostomy Bag	Colostomy bag pouch should be shaped in such a way that it guarantees a perfect fit at all times. The closed pouches should contain protected filter and hydrocolloid skin-protection. Pouch size: 5 1/8" x 7 1/2" (130mm x 190mm) Cut to fit range: 3/4" - 2" (20 - 50 mm) Adhesive surface: 4 3/8" - 4 3/8" (110mm x 110mm) Color: skin-colored			
17	Gigli Saw Wire	Made of martensitic steel (quenched, magnetic steel) and not stainless steel. Hooks at both ends. Should conform to ISO standard			

18	Rebreathing Bag All Size	Should be made of non toxic, latex free material (Green/Black), with proper fix to the breathing circuit connector. Resistance: 5x104 / 5x106 ohms. 5602/BS 3353 standard .Capacity (All size).			
19	Asepto Syringe	Feeding and irrigation syringe pump. Tapered tip facilitates easy and safe connection to any catheter or gastric tube. Transparent bulb facilitates easy pumping and suction. Sterile, individually packed in a peelable pouch. Capacity 60ml			
20	Clinical Thermometer	1. Measuring Range 32.0~44.0 $^{\circ}$ C(89.6~111.2 $^{\circ}$ F); 2. Accuracy: $\pm$ 0.1 $^{\circ}$ C($\pm$ 0.2 $^{\circ}$ F) for 35.0~42.0 $^{\circ}$ C(95.0~107.6 $^{\circ}$ F); $\pm$ 0.2 $^{\circ}$ C ($\pm$ 0.4 $^{\circ}$ F) for remaining range at an ambient of 22 $^{\circ}$ C(71.6 $^{\circ}$ F); 3. Display: 3 1/2 LCD digits (Unit of display: 0.1 $^{\circ}$ C/0.1 $^{\circ}$ F); 4. Battery: LR41 alkaline; Battery life: About 250 hours or 1000 times; 5. Fever alarm; Waterproof case; 6. Memory for last measurement; 6. Low battery indication; Automatic power off; 7. Unit size: 120*20*12mm; Weight: 10.6g.			
21	Rubber Tourniquet	Rubber Tourniquet			
22	Transducer Protector	1. Transducer Protector connects blood tubing with dialysis machine. 2. Protective hydrophobic barrier allows only sterile air to pass through, protecting patients and equipment from cross contamination. 3. Prevents blood and dialyzing fluid from damaging sensitive Transducer Monitoring Devices 4. The transducer protector used in dialysis is of PTFE material (hydrophobic membrane) 5. Pore sizes are typically 0.2 μ m (the purpose of this would be to push the contaminated blood into the dialysis filtration unit, in doing so one would require pre-filters of minute sizes). 6. Efficient filter area 3.1 cm ² 7. Max pressure 0.3 MPa 8. working temp 60 $^{\circ}$ C 9. PTFE double layer working pressure : $\leq$ 150Kpa This membrane is sealed to a Poly carbonate casing by Ultrasonic welding.			
23	Wolf Bottle	Wolf Bottle			
24	Bivalve (Three way)	1. The stopcock should be manufactured from medical grade, clear transparent lipid compliant polycarbonate 2. Its three arm handle should be easy to operate 3. The device should allow for minimum residual volume 4. There should be a rigid stopcock with circular flow-channel prevents the incidence of air-trap 5. It should be provided with two female luer lock ports and one male luer lock port with rotating lock, for safe connection to other device 6. It should be sterile and individually packed in blister pack plastic with leur lock & side connection			
25	Foley Catheter (All Size)	Should be made of silicone-coated natural latex. Should consist of a hollow 2-way cylindrical tube with: 1. Central channel for urinary drainage. 2. Bladder side should end in a round or cylindrical atraumatic tip with 2 opposing eyelets. 3. Collector side should have a universal and hollow truncated cone (funnel) to connect the urine bag, spigot, syringe or irrigating device. 4. One side channel for balloon inflation: ending in a non-return valve with a Luer connection and 1 inflatable balloon. Length : 360mm adults Diameter ranges: adults 12mm to 20mm Balloon expansion capacity: children 3-5ml; adults 15ml Catheter size and balloon capacity must be indicated on the catheter. For safety, the catheter must be double packaged.			

26	Sterile HIV Kit	COMPLETE PROTECTION KIT – Includes gown, goggles, gloves, cap, mask, leg cover, and towels—ensuring full-body safety during surgical and high-risk procedures. PREMIUM SURGICAL GOWN – 50 GSM SMS trilaminate gown offers excellent bacterial filtration, fluid resistance, and tear-proof strength for reliable infection control. EYESAFE GOGGLES – Anti-fog, anti-glare, and wearable over prescription glasses, these goggles shield eyes from splashes and airborne contaminants. STERILE GLOVES INCLUDED – Ergonomically designed gloves offer secure protection with superior grip and tactile precision during medical tasks. BREATHABLE FACE MASK – Multi-layer disposable mask provides secure nose-to-chin coverage with airflow comfort for extended wear.			
27	CPAP Mask	1. The mask should have headgear with a provision to support on the patient face and reduce excess pressure on the patient's nose bridge. 2. Should have provision to maintain 12mm gap between forehead and mask nose bridge frame. 3. The headgear should have an option of providing a personalized fit to help increase comfort and tolerance for patients. 4. Headgear should help in easy sizing fitting and readjusting. 5. Mask should have auto adjusting seal and come with a sizing guide to choose right size for patients. 6. Should have provision for slot for Oro-Naso-Gastric Tubes.			
28	Ventilator Circuit (Paediatric & Neonatal)	A dual-limb, heated infant breathing circuit designed for neonatal invasive ventilation. Made for flows > 4 L/min, it delivers consistent humidity without condensate buildup. It allows water vapor to escape through the expiratory tubing wall, preventing condensation, reducing alarms, and maintaining a closed system.			
29	Stellate (Skin Grafting Blade)	Stainless steel blade, sharp blade edge should offer smooth shaving of healthy skin tissue, Individually sterile packed, European CE certified, Expiry date should be written.			
30	Feeding Tube (All Size)	For neonatal and paediatric nutritional feeding. Should be made of non toxic PVC material. Should have a closed distal end with two lateral eyes. Tube with radio-opaque line, marked at 25 cms from the tip for accurate placement. Soft and rounded tip to prevent trauma during application. Soft, frosted and kink resistant PVC tubing. Radio Opaque line is provided throughout the length for X-Ray visualisation. Proximal end is fitted with female luer mount for easy connection to feeding funnel or syringe. Colour coded for size identification. Also available with Luer Lock. Sterile product for single use. Straight package required, no coiled package.			
31	Plasma Filter	Plasma Filter : dry Membrane material - Polysulfone, Inner diameter-330 um, Wall thickness-65um, Housing material-Polycarbonate, Potting compound-Polyurethane, O-ring-Silicone, Sterilisation Method-Inline steam, Blood connectors Filtrate connectors-Compatible with ISO 8637-2, S(Sieving Coefficient)-Albumin-0.90, IGM-0.90, LDL-0.90, Maximum Filtrate flow-30% of effective blood flow, Recom. blood range* 9mL/min)-40-150/80-250, Max. TMP(mmHg)-100, V(prim. volume) Blood/Filtrate(mL-mL)35/90-67/160, P(press. drop blood, Hct, 45% (mmHg)70 (Q8=150mL/Min)/60(Q8=250mL/min)A(effective surface area (m2)-0.3/0.6			
32	Extension Line 10 cm	Extension Line 10 cm			

33	ECG Jelly	Should have neutral pH, be easy to spread, formaldehyde and salt free, nongreasy, proper adhesion for electrodes, easy squeeze leakproof bottle 250ml quantity, hypoallergenic, nontoxic odourless, high viscosity, high conductivity, water soluble, non staining easy to clean, non irritant to skin. Propylene glycol, Glycerine and phenoxyethanol containing gel Volume 250ml in compressible dispenser			
34	USG Jelly	Should have neutral pH, be easy to spread, formaldehyde and salt free, nongreasy, proper adhesion for electrodes, easy squeeze leakproof bottle 250ml quantity, hypoallergenic, nontoxic odourless, high viscosity, high conductivity, water soluble, non staining easy to clean, non irritant to skin. Propylene glycol, Glycerine and phenoxyethanol containing gel Volume 250ml in compressible dispenser			

Instructions and terms & condition regarding Quotation:-

1. Interested vendors should submit the quotation as per given format only. **Vendors need to specify Manufacturer & brand in the quotation and technical documents and the same supply needs to be supplied.**
2. Quotations must be submitted in a sealed envelope only. **Technical Documents and Financial Bid need to be submitted in separate envelope (Two Envelope Bid). Both Technical and Financial Bid in single envelope will be rejected.**
3. Both the envelopes should be addressed to - The Dean, Sir J J Group of Hospitals, Mumbai and **marked Kind attention to-Surgical store.**
4. **Vendors must write quotation reference no & Last date of submission of quotation on the envelope.**
5. Any amendments regarding the quotation will be published on website www.ggmchh.in. Vendors will not be communicated separately regarding the amendments. However if the vendor fails to check any of these amendments on the website then it will be presumed that the vendor has quoted his/ her rates by taking the note of these amendments.
6. Rate should be quoted **inclusive of all taxes .GST , etc.**
7. Rate must be written in both figures & words. Rates should be valid for six months from the date of opening the quotation.
8. Rate must be quoted for Surgical Items & Instrument complying with the standards for Surgical Items & Instruments (ISO/ISI, etc. whichever is applicable)
9. Delivery period is 24 hrs to 03 (Three) days from the receipt of order, as per vitality of Surgical items.
10. Analysis test reports (**Inhouse and NABL**) need to be submitted at the time of goods supply,
11. For goods supplied under MJPJAY Other schemes , bills will be passed only after the utilization certificate is received.
12. Successful vendors if fails to supply the goods within stipulated delivery period he is liable for the further necessary action, which may deem fit.
13. Frequent defaulter bidder will be debarred from participating in the future tenders /quotations called by this office
14. **Demo Sample will be required to be submitted to Surgical Store, Sir J J Group of Hospitals, Mumbai** for all quoted items whenever communicated. The submitted material will not be returned back to the vendor irrespective of qualification or disqualification
15. **Following documents need to be submitted along with quotation- (To be submitted in Separate Envelope)**
 - Bidders FDA, wholesale stocking & Selling Licence
 - Medical Device Licence for quoted Items (**clearly highlighting the item quoted**)
 - **Manufacturers Authorization Letter is mandatory for all above mentioned products.**
 - Non conviction certificate from FDA
 - GST registration copy
 - Bidder details as per Annexure A
 - Documents relating to past experience of supply in Government/Semi Government institutions.
 - Adata (अदाता) Registration Number at JJ Hospital Mumbai
 - WHO GMP certificate of manufacturer, ISO/ISI/CE/EN/ASTM Product Standard Certificate whichever is applicable

NOTE : Last date of submission of quotation: 24 / 07 /2026 before 5.00 pm



**Dean
Sir J J Group of Hospitals,
Mumbai**

Annexure – A

(To be submitted on Bidder's Letterhead, Incomplete Annexure is liable for Rejection)

1. Name and address of the firm: -
2. Registered Head Office Postal address: -
3. Telephone No.
4. E-Mail ID : -
5. Ownership status of the firm- (Maharashtra Govt. / Central Govt./Jt. Sector /co - operative /SSI /Private)
6. Whether bidding as a manufacturer / importer / Authorized Distributor
7. Name of the person & Phone no. who should be contacted by this office in case of emergency.
8. Payee (अदाता) Registration Number at Sir J J Hospital, Mumbai.
9. Bank Details: -
 - 1) Bank A/C No. _____
 - 2) IFSC Code: - _____
 - 3) Branch Name & Address: _____
 - 4) Cancelled Cheque: _____
10. PAN number _____
11. GST registration number _____

I / we hereby declare that particulars furnished above are true to the best of my /our knowledge and belief and that if any of the particulars is found to be materially incorrect / misleading, My /Our quotation shall be rejected. I / we accept all term & condition, also I / we are liable for penal action as per terms specified in the “ terms and conditions of quotation”.

Date: -

Signature of the bidder with official seal and address

ANNEXURE B

Technical Compliance Chart for Quoted Items

Sr No	Name of Item	Specification	Mfg. Name	Generic name/ brand name	Medical Device Lic. No.	MD Licence Page no.
1	Disposable Syringe 50ml	Single Use. Sterile. No leakage. Non traumatic plunger. Latex free. Non toxic. Non pyrogenic. BP/ISO/ISI /CE STANDARDS 50 ml				
2	T-Piece	For use in recovery for the delivery of oxygen - Connects to 15 mm ET tube connector/ laryngeal mask - Fitted with 22 mm male / 15 mm female patient port - 6" flexible corrugated tube oxygen reservoir with oxygen supply port along with cap - Sterile and individually packed				
3	Epidural Set No.18	1. Epidural Catheter should be made up of polyurethane with radiopaque line, open distal tip or closed distal tip with 3 laterals eyes. Markings every centimetre from 5 to 20cm from the distal tip. 2. 1 catheter connector Easy-lock type 3. 1 Tuohy needle - 90mm long, with plastic hub 4.1 Catheter guide which connects into the needle hub and facilitates the insertion of the catheter into the epidural space 1. Epidural Catheter should be made up of polyurethane with radiopaque line, open distal tip or closed distal tip with 3 laterals eyes. Markings every centimetre from 5.5 , smudged marked at 11cm from the distal tip. 2. 1 catheter connector Easy-lock type 3. 1 Tuohy needle - 90mm long, with plastic hub 4.1 Catheter guide which connects into the needle hub and facilitates the insertion of the catheter into the epidural space 5. 0.2 Åµm flat filter 6. 10ml syringe for loss of resistance(LOR) technique 7. 1 label for catheter identification Size:18G				
4	Laryngoscope Adult	Should be LED laryngoscope set, adult, macintosh type, Stainless steel blades with removable led lamp. Handle and blades are made of 304 grade stainless steel.Dull/matt finish. Supplied with 4 blades size 1, 2, 3 and 4 and two batteries for handle. Should provide with 1 spare led lamp and batteries				
5	Laryngoscope Paediatric	Should be LED laryngoscope set, adult, Miller Type, Stainless steel blades with removable led lamp. Handle and blades are made of 304 grade stainless steel.Dull/matt finish. Supplied with 4 blades size 0,00,1 and 2, two batteries for handle. Should provide with 1 spare led lamp and batteries.				
6	Intercostal Draining System (All size)	Catheter should be provided with trocar for easy penetration and flat handle of a trocar catheter for easy maneuverability and controlled insertion. Catheter should be kink-resistant smooth finish PVC with streamline,radio-opaque line,flat handle to facilitate easy maneuverability,markings provided at 5, 10, 15 and 20 cm from the distal tip to help ascertain the depth of penetration.Thermosensitive material used in these equipments softens with body temperature.Safety stop in cannula with tip-to-toe radiopaque strip. Proximal end should be fitted with an universal tapered connector for easy connection to the drainage bag.Water sealed drainage system for interostat drainage , sterile pyrogen free disposable (I C D Bags) bag. Should be available sterile, individually double packed in a peelable pouch. (Intercostal draining system with trocar and bag size-All size				

7	Swivel Mount Catheter	Flexible, light weight, corrugated or smooth bore, PVC tube (often 15 cm length) used to connect endotracheal / tracheostomy tubes to breathing circuit. 22mm standard female/15mm male patient-end swivel connector, 15mm/22mm circuit end connector, low dead space and optical luer lock ports for gas sampling.				
8	Biopsy Gun All Size	Automated spring Loaded core Biopsy instrument disposable Constructed from medical-grade stainless steel with plastic or lightweight metal housings. needle gauges 16G-20G, Needle Lengths 10cm-25cm, penetration depths 10mm-22mm, Sample Notch- Often 1.8 cm to 2.0 cm.				
9	Scalp Vein Set (All Size)	Sterile, siliconised, thin walled, short bevel needle with colour coded butterfly 20g				
10	Endotracheal Tube No. 5,5.5,6	Should be available as a transparent tube with radiopaque line in extra-soft PVC. The distal end of the tube should be bevelled at 37° - 10°. The tube should have clear distance markings A standard male ISO adaptor 15 mm to connect the endotracheal tube to the ventilator The distal end of the tube should be bevelled at 37°-10 5mm, 5.5mm, 6mm ID				
11	Sterile Disposable Needle All Size	Single use Sterile, surface should be extremely smooth, the needle point is extremely sharp. Color coded, individually blister packed, hypodermic needle 1 Inch				
12	PICC Catheter 4Fr	Intracavitary ECG derivation device CT easy with pressure injection up to 5cc/s and 325 PSI with radiopaque biostable PUR 4FR-600mm with NDD technique & Metallic stylet with repair kit. Safety Echogenic introducer needle 21G x 7cm • 1 straight Nitinol guidewire 0.46*50cm • Should be European CE Certified.				
13	Anatomical Face Mask 0,1,2,3,4	an inflatable cuff for comfort, a standard 22mm connector, and a disposable or autoclavable (up to 137°C) design, typically made from non-toxic silicone or PVC. 0,1,2,3,4				
14	Surgical Blade (All Size)	Surgical Blade / B.P. Blade Pre sterile wrapped with antirust paper in aluminium foil I S I mark No. (All Size) Surgical Blades Pre-Sterile With Gamma Radiation For Handle No. 4 Size CE certified				
15	Irrigation Balloon	Irrigation Balloon				
16	Colostomy Bag	Colostomy bag pouch should be shaped in such a way that it guarantees a perfect fit at all times. The closed pouches should contain protected filter and hydrocolloid skin-protection. Pouch size: 5 1/8" x 7 1/2" (130mm x 190mm) Cut to fit range: 3/4" to 2" (20 to 50 mm) Adhesive surface: 4 3/8" x 4 3/8" (110mm x 110mm) Color: skin-colored				
17	Gigli Saw Wire	Made of martensitic steel (quenched, magnetic steel) and not stainless steel. Hooks at both ends. Should conform to ISO standard				
18	Rebreathing Bag All Size	Should be made of non toxic, latex free material (Green/Black), with proper fix to the breathing circuit connector. Resistance: 5x104 / 5x106 ohms. 5602/BS 3353 standard .Capacity (All size).				
19	Asepto Syringe	Feeding and irrigation syringe pump. Tapered tip facilitates easy and safe connection to any catheter or gastric tube. Transparent bulb facilitates easy pumping and suction. Sterile, individually packed in a peelable pouch. Capacity 60ml				

20	Clinical Thermometer	1. Measuring Range 32.0~44.0°C(89.6~111.2°F); 2. Accuracy: $\pm$0.1°C($\pm$0.2°F) for 35.0~42.0°C(95.0~107.6°F); $\pm$0.2°C ($\pm$0.4°F) for remaining range at an ambient of 22°C(71.6°F); 3. Display: 3 1/2 LCD digits (Unit of display: 0.1°C/0.1°F); 4. Battery: LR41 alkaline; Battery life: About 250 hours or 1000 times; 5. Fever alarm; Waterproof case; 6. Memory for last measurement; 6. Low battery indication; Automatic power off; 7. Unit size: 120*20*12mm; Weight: 10.6g.				
21	Rubber Tourniquet	Rubber Tourniquet				
22	Transducer Protector	1. Transducer Protector connects blood tubing with dialysis machine. 2. Protective hydrophobic barrier allows only sterile air to pass through, protecting patients and equipment from cross contamination. 3. Prevents blood and dialyzing fluid from damaging sensitive Transducer Monitoring Devices 4. The transducer protector used in dialysis is of PTFE material (hydrophobic membrane) 5. Pore sizes are typically 0.2 μm (the purpose of this would be to push the contaminated blood into the dialysis filtration unit, in doing so one would require pre-filters of minute sizes). 6. Efficient filter area 3.1 cm² 7. Max pressure 0.3 MPa 8. working temp 60°C 9. PTFE double layer working pressure : $\leq$150Kpa This membrane is sealed to a Poly carbonate casing by Ultrasonic welding.				
23	Wolf Bottle	Wolf Bottle				
24	Bivalve (Three way)	1. The stopcock should be manufactured from medical grade, clear transparent lipid compliant polycarbonate 2. Its three arm handle should be easy to operate 3. The device should allow for minimum residual volume 4. There should be a rigid stopcock with circular flow-channel prevents the incidence of air-trap 5. It should be provided with two female luer lock ports and one male luer lock port with rotating lock, for safe connection to other device 6. It should be sterile and individually packed in blister packplastic with leur lock & side connection				
25	Foley Catheter (All Size)	Should be made of silicone-coated natural latex. Should consist of a hollow 2-way cylindrical tube with: 1. Central channel for urinary drainage. 2. Bladder side should end in a round or cylindrical atraumatic tip with 2 opposing eyelets. 3. Collector side should have a universal and hollow truncated cone (funnel) to connect the urine bag, spigot, syringe or irrigating device. 4. One side channel for balloon inflation: ending in a non-return valve with a Luer connection and 1 inflatable balloon. Length : 360mm adults Diameter ranges: adults 12mm to 20mm Balloon expansion capacity: children 3-5ml; adults 15ml Catheter size and balloon capacity must be indicated on the catheter. For safety, the catheter must be double packaged.				

26	Sterile HIV Kit	COMPLETE PROTECTION KIT – Includes gown, goggles, gloves, cap, mask, leg cover, and towels—ensuring full-body safety during surgical and high-risk procedures. PREMIUM SURGICAL GOWN – 50 GSM SMS trilaminate gown offers excellent bacterial filtration, fluid resistance, and tear-proof strength for reliable infection control. EYESAFE GOGGLES – Anti-fog, anti-glare, and wearable over prescription glasses, these goggles shield eyes from splashes and airborne contaminants. STERILE GLOVES INCLUDED – Ergonomically designed gloves offer secure protection with superior grip and tactile precision during medical tasks. BREATHABLE FACE MASK – Multi-layer disposable mask provides secure nose-to-chin coverage with airflow comfort for extended wear.				
27	CPAP Mask	1. The mask should have headgear with a provision to support on the patient face and reduce excess pressure on the patient's nose bridge. 2. Should have provision to maintain 12mm gap between forehead and mask nose bridge frame. 3. The headgear should have an option of providing a personalized fit to help increase comfort and tolerance for patients. 4. Headgear should help in easy sizing fitting and readjusting. 5. Mask should have auto adjusting seal and come with a sizing guide to choose right size for patients. 6. Should have provision for slot for Oro-Naso-Gastric Tubes.				
28	Ventilator Circuit (Paediatric & Neonatal)	A dual-limb, heated infant breathing circuit designed for neonatal invasive ventilation. Made for flows > 4 L/min, it delivers consistent humidity without condensate buildup. It allows water vapor to escape through the expiratory tubing wall, preventing condensation, reducing alarms, and maintaining a closed system.				
29	Stellate (Skin Grafting Blade)	Stainless steel blade, sharp blade edge should offer smooth shaving of healthy skin tissue, Individually sterile packed, european CE certified, Expiry date should be written.				
30	Feeding Tube (All Size)	For neonatal and paediatric nutritional feeding, Should be made of non toxic PVC material Should have a closed distal end with two lateral eyes Tube with radio-opaque line, marked at 25 cms from the tip for accurate placement Soft and rounded tip to prevent trauma during application Soft, frosted and kink resistant PVC tubing Radio Opaque line is provided throughout the length for X-Ray visualisation Proximal end is fitted with female luer mount for easy connection to feeding funnel or syringe Colour coded for size identification Also available with Luer Lock Sterile product for single use. Straight package required, no coiled package.				
31	Plasma Filter	Plasma Filter : dry Membrane material - Polysulfone , Inner diameter-330 um, Wall thickness-65um, Housing material-Polycarbonate, Potting compound-Polyurethane, O-ring-Silicone, Sterilisation Method-Inline steam, Blood connectors Filtrate connectors-Compatible with ISO 8637-2, S(Sieving Coefficient)-Albumin-0.90, IGM-0.90 ldl-0.90, Maximum Filtrate flow-30%fo effective blood flow, Recom. blood range* 9mL/min)-40-150/80-250, Max. TMP(mmHG)-100, V(prim. volume) Blood/Filtrate(mL-mL)35/90-67/160, P(press. drop blood, Hct, 45% (mmHg)70 (Q8=150mL/Min)/60(Q8=250mL/min)A(effective surface area (m2)-0.3/0.6				
32	Extension Line 10 cm	Extension Line 10 cm				

33	ECG Jelly	Should have neutral pH, be easy to spread, formaldehyde and salt free, nongreasy, proper adhesion for electrodes, easy squeeze leakproof bottle 250ml quantity, hypoallergenic, nontoxic odourless, high viscosity, high conductivity, water soluble, non staining easy to clean, non irritant to skin. Propylene glycol, Glycerine and phenoxyethanol containing gel Volume 250ml in compressible dispenser				
34	USG Jelly	Should have neutral pH, be easy to spread, formaldehyde and salt free, nongreasy, proper adhesion for electrodes, easy squeeze leakproof bottle 250ml quantity, hypoallergenic, nontoxic odourless, high viscosity, high conductivity, water soluble, non staining easy to clean, non irritant to skin. Propylene glycol, Glycerine and phenoxyethanol containing gel Volume 250ml in compressible dispenser				